

ALTECO®**PRO
SERIES**

HI-TEMP RTV SILICONE GASKET MAKER

DURABLE ▼

GOOD ADHESION ▼

PRESSURE RESISTANT ▼

RESISTANT TO VIBRATION ▼

BLACK**BLUE****RED****GREY**

ALTECO HI-TEMP RTV SILICONE GASKET MAKER is a solvent free, elastic, room temperature curing compound designed to deliver reliable "formed-in-place" gaskets for assembling machine parts that resists weathering and thermal cycling without cracking, shrinking and migration. Ideal as replacement for gasket, seal, gasket dressing, cork and felt. It's stable at temperatures from -62°C to 343°C (-80°F to 650°F).

Application Area: Valve Covers, Oil Pans, Timing Covers, Water Pumps, Transmission Pans, etc.

Directions:

1. Surface must be clean and dry.
2. Pierce end tube using cap and install nozzle.
3. Apply even and continuous bead to one surface. Allow sealant to skin before assembling.
4. To remove excess uncured sealant with mineral turpentine. Fully cured excess sealant can be removed by knife.
5. Clean away excess material from nozzle and replace with cap immediately after use.
6. Allow to cure overnight for best result.

** for Red & Grey types only*



ALTECO CHEMICAL PTE LTD
[A Member of ALTECO Group of Companies, Japan]

Linking Links Trading Enterprise
Southern Africa Distributor
Email: info@linkinglinks.co.za

Distributed by

Linking
LINKS



PO Box 101, Wierda Park, Centurion 0149
Cell: + 27 (0) 74 819 8803 or + 27 (0) 84 648 9102
Tel: +27 (0) 12 771 2557 - Fax2Mail: 086 604 8058

ALTECO®

NEW

HI-TEMP RTV SILICONE GASKET MAKER



Ideal for
**AUTOMOTIVE AND INDUSTRIAL
APPLICATIONS**

Resists Aging, Weathering and Thermal Cycling without Shrinking or Cracking

LEAK-PROOF

GOOD ELASTICITY

EXCELLENT OIL,
WATER RESISTANCE

HIGH TEMPERATURE
RESISTANCE UP TO
343°C (650°F)